



MPL Products
26 Baddesley Way
Canning Vale, Western Australia
Australia, Post Code – 6155
ph: +61421837661
email: mplexim61@gmail.com

PRODUCT DATA SHEET

SBR Latex

PRODUCT DESCRIPTION:

SBR LATEX is a Styrene-Butadiene Latex used for modification of hydraulic binders. The dispersion is free from plastisizers and film forming aids. It is manufactured by employing state-of-the-art emulsion polymerization technology ensuring product consistency.

TYPICAL PHYSICAL PROPERTIES

Properties	Specification
Appearance	White milky liquid
Specific Gravity	1.02-1.08
pH	7-9
Solubility	Soluble in water

APPLICATION/ADVANTAGES

- Hydraulic cement admixture, flexible cementitious waterproofing coatings, oil well cementing.
- High resistance to alkaline hydrolysis Provides excellent water impermeability and chemical resistance.
- Excellent workability at reduced water/ cement ratio.
- Improved bonding and adhesion to substrate.
- Excellent stability against electrolytes.
- Provides freeze/thaw resistance.

ENVIRONMENTAL INFORMATION:

For information concerning environmental regulation applicable to this product, Contact the Health Safety and Environmental Department.

SHIPPING:

Transportation of Commodity name is not restricted by either international or INDIA regulatory Agencies.

SAFE HANDLING RECOMMENDATIONS:

Utilize normal precautions for employee protection when handling chemical products. Use of standard PPE is recommended for employee comfort and safety.
See material safety data sheet (MSDS) prior to use.

PACKAGING:

SBR LATEX isP packaged in 55 Gal Drums & 5 Gal Pails. Customized packing can be done as per the requirements.